



**NOTE:**

- 1) MOUNTING HARDWARE REQUIRED
- 2) SUGGESTED MTG. HOLE =  $\phi$ .147



LEAD FINISH: SILVER	
BUSHING FINISH: SILVER	
CAPACITANCE	5500pF GMV
TEMP. RANGE	-55°C TO 125°C
CURRENT	3 AMP MAX.
WORKING VOLTAGE	125°C 50VDC MAX.
D.C. RESISTANCE	.01ohms MAX.
MIN. I.L. PER MIL-STD-220 AT 25°C NO LOAD	
FREQ. MHz	I.L. (db)
3	7
10	14
30	30
100	55
300	70
1GHz	70



**MARKING:**

PART: S008 (FAIRVIEW)  
S008M (MEXICO)

BAG: 51-726-008  
DATE CODE  
LOT NO.  
QTY/PACK  
(50/BAG MAX.)



	39		REV. NO.	TOLERANCES UNLESS OTHERWISE SPECIFIED		FAIRVIEW PENNSYLVANIA
	38		CHANGE NOTICE	Fractions $\pm 1/64$		
	CN #17667			Dec. .xx±	Date 01-05-16	
	CN 213478			Dec. .xxx±.010	Engr. M.McALEVY	
	CN 201675			Angles $\pm 0^{\circ} 30'$	Scale NONE	
	CN 201518			CODE IDENT. NO. QLSP2	51-726-008	
	CN 184882 REDRAWN					