

$\phi.030$
 $\pm.002$
[0.76]


NOTES:

1. SUGGESTED MOUNTING HOLE = $\phi.130$




LEAD FINISH: GOLD PL.	
CASING FINISH: GOLD PL.	
CAPACITANCE	10nF MIN.
TEMP. RANGE	-55°C TO 125°C
CURRENT	10 AMP MAX.
WORKING VOLTAGE	125°C -- VAC MAX. 125°C 200 VDC MAX.
D.C. RESISTANCE	.01ohms MAX.
MIN. I.L. PER MIL-STD-220 AT 25°C NO LOAD	
FREQ. MHz	I.L. (db)
1	8
10	27
100	48
1 GHz	65
10 GHz	65

SCHEMATIC



MARKING:

PART: 2 WHITE COLOR DOTS
BAG:
SCI-9980-103
DATE CODE
LOT NO.
QTY/BAG (200 MAX.)

	00	REV. NO.	TOLERANCES UNLESS OTHERWISE SPECIFIED	 FAIRVIEW PENNSYLVANIA SPECTRUM CONTROL INC.
	CN 53138-ENG	CHANGE NOTICE	Fractions $\pm 1/64$	
			Dec. .xx \pm	Dwn. KAUFFMAN
			Dec. .xxx $\pm.005$	Date 3-01-10
			Angles $\pm 0^{\circ} 30'$	Engr. B. DEVINE
			CODE IDENT. NO. DLSP2	Scale NONE
				Description FEEDTHRU FILTER
				SCI-9980-103