

## Type 3 surge protection plug - PLT-SEC-T3-60-P - 2905233

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Replacement plug for type 3 device protection from the PLUGTRAB SEC T3 product range. 60 V nominal voltage.

The illustration shows version PLT-SEC-T3-230-P

### Product Features

- Varistor-based device protection
- Can be used without separate backup fuse thanks to integrated overcurrent protection
- Pluggable
- Optical status indicator via LED
- Plugs can be checked with CHECKMASTER 2



### Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	40.0 g
Custom tariff number	85363030
Country of origin	Germany

### Technical data

#### Dimensions

Height	60.9 mm
Width	17.5 mm
Depth	44.8 mm
Horizontal pitch	1 Div.

#### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 80 °C
Ambient temperature (storage/transport)	-40 °C ... 80 °C

# Type 3 surge protection plug - PLT-SEC-T3-60-P - 2905233

## Technical data

### Ambient conditions

Altitude	≤ 2000 m (amsl (above mean sea level))
Permissible humidity (operation)	5 % ... 95 %
Shock (operation)	30g (half sinus / 11 ms / 3x ±X, ±Y, ±Z)
Vibration (operation)	5g (10 ... 150 Hz/20 cycles/axis/X, Y, Z)

### General

Standards/specifications	EN 61643-11 2012
IEC test classification	III
	T3
EN type	T3
SPD design	Combination type
Mode of protection	L-N
	L-PE
	N-PE
	(L+) - (L-)
	(L+/L-) - PE
Mounting type	On base element
Color	light grey RAL 7035
Housing material	PA 6.6-FR 20% GF
	PA 6.6-FR
Pollution degree	2
Flammability rating according to UL 94	V-0
Type	Male
Number of positions	2
Surge protection fault message	optical

### Protective circuit

Nominal voltage $U_N$	60 V AC (TN-S)
Nominal frequency $f_N$	50 Hz (60 Hz)
Maximum continuous voltage $U_C$	100 V AC
	80 V DC
Residual current $I_{PE}$	≤ 5 μA
Nominal discharge current $I_n$ (8/20) μs	2 kA
Standby power consumption $P_C$	≤ 75 mVA (at $U_{REF}$ )
	≤ 150 mVA (at $U_C$ )
Reference test voltage $U_{REF}$	66 V AC
Combination wave $U_{OC}$	4 kV
Voltage protection level $U_p$ (L-N)	≤ 0.48 kV

## Type 3 surge protection plug - PLT-SEC-T3-60-P - 2905233

### Technical data

#### Protective circuit

Voltage protection level $U_p$ (L-PE)	$\leq 0.9$ kV
Voltage protection level $U_p$ (N-PE)	$\leq 0.9$ kV
TOV behavior at $U_T$ (L-N)	120 V AC (5 s / withstand mode)
	120 V AC (120 min / withstand mode)
TOV behavior at $U_T$ (L-PE)	120 V AC (5 s / withstand mode)
	120 V AC (120 min / withstand mode)
Response time $t_A$ (L-N)	$\leq 25$ ns
Response time $t_A$ (L-PE)	$\leq 100$ ns
Response time $t_A$ (N-PE)	$\leq 100$ ns
Short-circuit current rating $I_{SCCR}$	1.5 kA AC
	1 kA DC

#### UL specifications

UL class	SPD type 4CA
Maximum continuous operating voltage MCOV	100 V AC
	80 V DC
Nominal voltage	60 V DC
Mode of protection	L-N
	L-G
	N-G
	(L+) - (L-)
	(L+) - G
	(L-) - G
Power distribution system	1
Nominal frequency	50/60 Hz
Measured limiting voltage MLV (L-N)	540 V
Measured limiting voltage MLV (L-G)	740 V
Measured limiting voltage MLV (N-G)	740 V
Measured limiting voltage MLV (L+) - (L-)	540 V
Measured limiting voltage MLV (L+) - G	740 V
Measured limiting voltage MLV (L-) - G	740 V
Nominal discharge current $I_n$	3 kA

### Classifications

eCl@ss

eCl@ss 5.1	27130801
------------	----------

# Type 3 surge protection plug - PLT-SEC-T3-60-P - 2905233

## Classifications

### eCl@ss

eCl@ss 6.0	27130806
eCl@ss 8.0	27130806

### ETIM

ETIM 5.0	EC000942
----------	----------

## Approvals

### Approvals

#### Approvals

KEMA-KEUR / CCA / UL Recognized / cUL Recognized / EAC / GL / cULus Recognized

#### Ex Approvals

UL Recognized / cUL Recognized / cULus Recognized


#### Approvals submitted

## Approval details

KEMA-KEUR 
---

CCA
-----

UL Recognized 
---


cUL Recognized 
--

EAC
-----

## Type 3 surge protection plug - PLT-SEC-T3-60-P - 2905233

### Approvals

GL

cULus Recognized 

### Accessories

#### Accessories

#### Device marking

Label - EML (20XE)R - 0803452



Label, Roll, white, unlabeled, can be labeled with: THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK X, THERMOMARK S1.1, Mounting type: Adhesive, Lettering field: continuous x 20 mm

Label - EML (20XE)R YE - 0803453



Label, Roll, yellow, unlabeled, can be labeled with: THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK X, THERMOMARK S1.1, Mounting type: Adhesive, Lettering field: continuous x 20 mm

### Additional products

Type 2 surge protection base element - PLT-SEC-T3-BE - 2905557




Base element for protective plugs from the PLUGTRAB SEC product series with remote indication contact.

### Drawings

## Type 3 surge protection plug - PLT-SEC-T3-60-P - 2905233

Circuit diagram



Dimensional drawing

