


KEMET Part Number: T429X157K010CC4252
(CWR29FC157KCXC)

Capacitor, Tantalum, 150 uF, 6954, +/-10% Tol, -55/+125C, 10 VDC (85C), Failure Rate=C (0.01%/1000 Hrs)



Dimensions (mm)		
Symbol	Dimension	Tolerance
L	6.93	+/-0.38
W	5.41	+/-0.38
H	2.74	+/-0.38
K	1.22	MIN
F	3.05	+/-0.13
S	1.19	+0.025/-0.13
P	0.61	MIN
A	4.55	NOM

Notes:

-Note: When Option C Is Selected For Lead Material, Add An Additional 0.38mm To The Tolerances For "L", "W", "H", "K", "F" And "S"

-P And R Dimensions Represents The Minimum Solderable Area Of The Termination Surface Entirely Below Cutout (If One Is Present)

General Information	
Supplier:	KEMET
Application:	MIL-PRF-55365/11
Part Type Description:	SMD, MnO2, Molded, Military Equivalent, Low ESR
Construction:	Standard Chip-MnO2
Body Type:	SMD Chip
Termination:	Hot Solder Dipped
Footprint:	6954
Weight:	590.44 mg
Approvals:	MIL-PRF-55365/11, CWR29 Style
RoHS:	No

Specifications	
Capacitance:	150 uF
Tolerance:	+/-10%
Voltage:	10 VDC (85C)
Voltage:	6.7 VDC (125C)
Temperature Range:	-55/+125C
Testing:	Surge Testing At -55C And +85C Before Weibull
Resistance/ESR:	0.065 Ohms (100kHz)
Failure Rate:	C (0.01%/1000 Hrs)
Leakage Current:	15 uA
Dissipation Factor:	10%

Packaging Specifications	
Package Kind:	T&R
Package Size:	7 in/180 mm
Package Quantity:	500